

# DUROTECH JOINT SEAL TAPE



Both side fleece coated NBR rubber elastic sealing tape with good lateral extension

## DESCRIPTION

Both side with non-woven coated NBR rubber elastic sealing tape with low textile content. The tape exhibits excellent recovery characteristics and is fully silicone compatible.

## APPLICATIONS

For use in corners and to cover joints for internal and external application.

## TECHNICAL INFORMATION

<b>Thickness</b>	0.60mm
<b>Width</b>	120mm
<b>Weight</b>	50g/m
<b>Equivalent air layer thickness sd</b>	5m
<b>Water pressure resistance</b>	Leakproof at 3 bar
<b>Elongation, lateral direction</b>	250%
<b>Elongation, lengthwise direction</b>	50%
<b>Temperature resistance</b>	-20°C to +90°C

## PREPARATION OF THE SUBSTRATE:

This will depend on the nature and form of the substrate and the sealing system to be used. A suitable primer should be first applied (see Table of Applications).

## CONSUMPTION

When calculating consumption, allow for a tape overlap of at least 5 cm.

## INFORMATION ON FURTHER PROCESSING:

The tape ensures excellent compatibility and good adhesion with polymer dispersions, flexible mineral sealing compounds and thermosetting resins. However, it is advisable to conduct a compatibility test before applying other products.

## CLEANING OF TOOLS AND EQUIPMENT:

Tools and soiled areas should be cleaned immediately after use with water.

## STORAGE

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

## SUPPLIED AS:

10 m roll	50 m roll
1 roll/carton	1 roll/carton
700 cartons/pallet	144 cartons/pallet



## USE

Cut the sealing tape to the required length and press onto the fresh Durotech sealing compound, which serves as the adhesive base. Ensure that there is a tape overlap of at least 5 cm. Use a smoothing trowel to level out any uneven areas or distortions. Apply two or three coats and ensure that the tape is fully covered with Durotech Sealing Compound or other sealants.

## DISPOSAL

May be disposed of as building site waste.

### VICTORIA

34 Indian Drive Keysborough  
Victoria 3173  
Tel: 1300 434 272  
[sales@durotechindustries.com.au](mailto:sales@durotechindustries.com.au)  
[www.durotechindustries.com.au](http://www.durotechindustries.com.au)

### NEW SOUTH WALES

14 Essex st, Minto, Sydney  
NSW 2566  
Tel: 1300 434 272  
[sales@durotechindustries.com.au](mailto:sales@durotechindustries.com.au)  
[www.durotechindustries.com.au](http://www.durotechindustries.com.au)

### QUEENSLAND

1/16 Export Drive, MOLENDINAR  
QLD 4214  
Tel: 1300 434 272  
[sales@durotechindustries.com.au](mailto:sales@durotechindustries.com.au)  
[www.durotechindustries.com.au](http://www.durotechindustries.com.au)

### SOUTH AUSTRALIA

30C Richard Street  
Hindmarsh, SA, 5007  
Tel: 1300 434 272  
[sales@durotechindustries.com.au](mailto:sales@durotechindustries.com.au)  
[www.durotechindustries.com.au](http://www.durotechindustries.com.au)

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses."

