

DUROFABRIC™ BUTYL SQUARE

SELF-ADHESIVE BUTYL FLOOR SLEEVE FOR A PERMANENT SEALING OF FLOOR DRAINS IN COMBINATION WITH SEALING SYSTEMS UNDER TILES IN WET ROOMS



DESCRIPTION

DUROFABRIC™ BUTYL SQUARE is a self-adhesive watertight, easy to handle butyl floor sleeve. The sleeve is made from butyl rubber with polypropylene fleece coated. This material basis causes an excellent bonding with almost any waterproofing materials used under tiles extending over the entire surface of the sleeve.

APPLICATION

Designed to create a permanent water repellent seal on the wall / floor around penetrations in walls and drainage areas in floors. DUROFABRIC™ BUTYL SQUARE is pressure sensitive there is no curing time required, so DUROTECH™ waterbased membranes may be laid immediately onto the non-woven fleece surface. DUROFABRIC™ BUTYL SQUARE is for use in all wet areas such as kitchens, bathroom, showers, external balconies & roofs as part of a full DUROTECH™ waterproofing system. DUROFABRIC™ BUTYL SQUARE offers major benefits in that it contains no volatile organic content, is highly resistant to detergents and bleaches and is compatible with the DUROSEAL HYBRID sealant range.

TECHNICAL SPECIFICATIONS

Total measurements: 370 x 370 mm
Measurements butyl: 300 x 300 mm
Thickness butyl: 1.0 mm
Temperature resistance: -40°C to +70°C

PREPARATION OF THE SUBSTRATE

Surfaces should be clean, dry and free from surface contaminants prior to application. Firm pressure should be applied across the entire surface and the use of a pressure roller is highly recommended. The split liner allows for easy application and it is recommended that application be carried out between 5°C and 40°C.

USE

Remove the protective backing sheet from one side and press the backing onto the surface ensure no air is trapped by using a pressure roller. Now remove the second half of the backing sheet and press the sheet completely onto the surface. DUROFABRIC™ BUTYL SQUARE can be instantly coated with DUROTECH™ waterproofing membranes.

INFORMATION ON FURTHER PROCESSING

Solvent-free adhesives and coatings may be applied directly onto the Durofabric Butyl Square. Before applying further products a compatibility test has to be carried out.



CLEANING OF TOOLS AND EQUIPMENT SUPPLIED AS

Tools and soiled areas should be cleaned immediately after use with water.

10 pieces / carton.

STORAGE

durofabric Butyl Square can be used for a period of at least 12 months when stored in a cool and dry period.

DISPOSAL

May be disposed of as building site waste.

VICTORIA

34 Indian Drive Keysborough
Victoria 3173
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

NEW SOUTH WALES

14 Essex st, Minto, Sydney
NSW 2566
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

QUEENSLAND

1/16 Export Drive, MOLENDINAR
QLD 4214
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

SOUTH AUSTRALIA

30C Richard Street
Hindmarsh, SA, 5007
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses."



@DUROTECHINDUSTRIES.COM.AU