

DUROFABRIC™ JOINT SEAL TAPE

DOUBLE-SIDE FLEECE COATED NBR RUBBER
ELASTIC SEALING TAPE WITH GOOD LATERAL EXTENSION



DESCRIPTION

DUROFABRIC™ JOINT SEAL TAPE is an innovative detailing system designed for waterproofing and sealing all types of joints, junctions and general areas subject to movement. Featuring the central “Flexible Zone” DUROFABRIC™ JOINT SEAL TAPE can accommodate movement in longitudinal, lateral and transverse directions enabling high elongation, rupture resistance, and up to 100% elastic recovery. DUROFABRIC JOINT SEAL TAPE is easy to install and provides for considerable time saving efficiencies and durable properties over conventional bond breaking sealants and tapes.

USE AREA

For use in corners to cover joints for internal and external application.

TECHNICAL INFORMATION

Thickness	0.60mm
Width	120mm
Weight	50g/m
Equivalent Air Layer Thickness Sd	5m
Water Pressure Resistance	Leakproof at 3 bar
Elongation, Lateral Direction	250%
Temperature Resistance	-20°C to +90°C

PREPARATION OF THE SUBSTRATE

This will depend on the nature and form of the substrate and the DUROTECH™ waterbased or cementitious waterproofing system to be used. A suitable primer should be first applied as per the DUROTECH™ waterbased or cementitious waterproofing system being used.

USE

Cut DUROFABRIC™ JOINT SEAL TAPE to the required length and press onto the fresh DUROTECH™ waterproofing membrane, which serves as the adhesive base. Ensure that there is a tape overlap of at least 5 cm. Use a smoothing trowel to level out any uneven areas or distortions. Apply two or three coats of the approved DUROTECH™ waterproofing membrane and ensure that the tape is fully coated



COMPATIBLE DUROTECH™ WATERPROOFING SYSTEMS

DUROFABRIC™ JOINT SEAL TAPE is compatible with the following DUROTECH™ waterproofing membranes as an elastomeric joint system, and forms part of a complete waterproofing system:

- DUROFLEX™ TANK
- DUROFLEX™ ACS - 2
- DUROFLEX™ 1K
- DUROTECH™ D400
- DUROMASTIC™ P15 DIAMOND
- DUROTECH™ 007FC
- DUROMASTIC™ DURAROOF

ASSOCIATED SYSTEM PRODUCTS

- DUROFABRIC™ PRE-FABRICATED CORNERS
- DUROFABRIC™ PIPE COLLAR

STORAGE

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

ROLL SIZE

120mm X 50m.

DISPOSAL

May be disposed of as building site waste.

VICTORIA

34 Indian Drive Keysborough
Victoria 3173
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

NEW SOUTH WALES

1 Prince William Drive, Seven Hills,
NSW, 2147
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

QUEENSLAND

1/16 Export Drive, MOLENDINAR
QLD 4214
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

SOUTH AUSTRALIA

30C Richard Street
Hindmarsh, SA, 5007
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

*This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses.



[@DUROTECHINDUSTRIES.COM.AU](http://www.durotechindustries.com.au)