

PRODUCT DATA SHEET

DUROFABRIC™ PIPE COLLAR

ELASTIC SLEEVE FOR A PERMANENT SEALING OF PIPE
PASSAGES IN COMBINATION WITH SEALING
SYSTEMS UNDER TILES.



DESCRIPTION

DUROFABRIC™ PIPE COLLAR is an innovative detailing system designed for waterproofing and sealing pipe penetrations. Featuring the central “Flexible Zone” DUROFABRIC™ PIPE COLLAR can accommodate movement in transverse directions enabling rupture resistance, and up to 100% elastic recovery. DUROFABRIC™ PIPE COLLAR is easy to install and provides for considerable time saving efficiencies and durable properties over conventional bond breaking sealants and tapes.

APPLICATIONS

For use over pipe penetrations.

TECHNICAL INFORMATION

Thickness: 0.60mm
Width & Length: 120mm x 120mm
Weight: 50g/m
Water pressure resistance: Leakproof at 3 bar
Temperature resistance: -20°C to +90°C

PREPARATION OF THE SUBSTRATE

This will depend on the nature and form of the substrate and the DUROTECH™ waterbased or cementitious waterproofing system to be used. A suitable primer should be first applied as per the DUROTECH™ waterbased or cementitious waterproofing system being used.

USE

DUROFABRIC™ PIPE COLLAR is suitable as permanently watertight sealing on wall areas for pipe passages of shower and bathtub water fittings under ceramic coverings. DUROFABRIC™ PIPE COLLAR is pressed onto the fresh DUROTECH™ waterproofing membrane, which serves as the adhesive base. Use a smoothing trowel to level out any uneven areas or distortions. Apply two or three coats of the approved DUROTECH™ waterproofing membrane and ensure that the collar is fully coated.

INFORMATION ON FURTHER PROCESSING

DUROFABRIC™ PIPE COLLAR is absolutely silicone-compatible; a soaking must not be expected. For lining the joints usual silicones may be applied. Solvent-free adhesives and coatings may be applied directly onto the DUROFABRIC™ PIPE COLLAR. Before applying further products a compatibility test has to be carried out.

CLEANING OF TOOLS AND EQUIPMENT

Tools and soiled areas should be cleaned immediately after use with water.

STORAGE

DUROFABRIC™ PIPE COLLAR can be used for a period of at least 24 months when stored in a cool and dry period.



COMPATIBLE DUROTECH™ WATERPROOFING SYSTEMS

DUROFABRIC™ PIPE COLLAR is compatible with the following DUROTECH™ waterproofing membranes and forms part of a complete waterproofing system:

- DUROFLEX™ TANK
- DUROFLEX™ ACS - 2
- DUROFLEX™ 1K
- DUROTECH™ D400
- DUROMASTIC™ P15 DIAMOND
- DUROTECH™ 007FC
- DUROMASTIC™ DURAROOF

ASSOCIATED SYSTEM PRODUCTS

- DUROFABRIC™ JOINT SEAL TAPE
- DUROFABRIC™ PRE-FABRICATED CORNERS

PACKAGING

20 units per box.

VICTORIA

34 Indian Drive Keysborough
Victoria 3173
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

NEW SOUTH WALES

1 Prince William Drive, Seven Hills,
NSW, 2147
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

QUEENSLAND

1/16 Export Drive, MOLENDINAR
QLD 4214
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

SOUTH AUSTRALIA

30C Richard Street
Hindmarsh, SA, 5007
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses."



@DUROTECHINDUSTRIES.COM.AU