

DUROPRIME™ RAPID

FAST CURE HI GRAB PRIMER



DESCRIPTION

DUROPRIME™ RAPID is a single component primer used to prime concrete, masonry and fibre cement sheeting surfaces. When dry, it forms a clear and or pink sealed surface suitable for the application of DUROSHEET™ BFM membrane.

FEATURES

- Fast drying, enabling a membrane application within 30 minutes
- Polymer based
- Ease of use
- Low odour
- Simple to apply
- Hi grab rapid cure

USE AREA

Concrete and Fibre-Cement.

PACKAGING

- 20 Litre

TECHNICAL INFORMATION

Colour	Red
Touch Dry Time	30 minutes at 25°C
Shelf Life	1 year stored in unopened container at 20°C

DESCRIPTION

All surfaces to be sound and clean; concrete to be free of efflorescence and contamination. Do not apply when temperature is above 30°C. Use a brush or roller for application. Clean equipment with DUROTECH™ XYLENE before it dries.

Smooth surface: 6 - 8 m/L

Rough/Porous surface: 3 - 4 m/L

PRECAUTIONS

- Do not use on glass or glazed surfaces
- Do not apply over curing compounds, wax/oily surface, fibreglass, plastic or silicone treated surfaces
- Not to be used as a primer for areas with rising moisture or negative hydrostatic pressure
- Not to be applied over raw steel or metals unless otherwise specified in this data sheet
- Contents should not be swallowed or inhaled. In case of eye contamination, rinse with clean water and seek medical advice
- Material Safety Data Sheet (MSDS) available
- For further information about this product contact technical department of Durotech Industries 1300 434 272.



NOTES

It is recommended before commencing the application; that adhesion of products to be used (e.g primers, membranes, coating adhesives etc) is tested over a typical area of the prepared surface to ensure satisfactory adhesion. It is the responsibility of the applicator to carry this out and accept the substrate suitability before any application starts. Durotech Industries offers a service for pre-testing adhesion to surfaces for large commercial areas or unusual substrates. For further details contact Durotech Industries.

Details contained in product data sheets are general. For any situation or items not covered in this data sheet, it is the responsibility of the applicator to check with Durotech Technical Services before commencing with the application. A written confirmation will then be issued by Durotech Technical Services.

CLEAN UP

CAUTION: Spills are difficult to remove. Wet tools can be cleaned with DUROTECH™ XYLENE. Do not allow any of these products to enter drains and waterways.

SAFETY & PRECAUTIONS

Refer to the DUOPRIME™ RAPID Material Safety Data Sheet available on the Durotech website. DUOPRIME™ RAPID is flammable. Keep all flames and ignition sources away from the product. The wearing of gloves, goggles, coveralls and safety footwear is highly recommended. DUOPRIME™ RAPID is a Class 3 dangerous goods which must be declared prior to transportation. For full safety details refer to the products Material Safety Data Sheet available on durotechindustries.com.au. For further information about this product contact technical department of Durotech Industries 1300 434 272.

VICTORIA

34 Indian Drive Keysborough
Victoria 3173
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

NEW SOUTH WALES

14 Essex st, Minto, Sydney
NSW 2566
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

QUEENSLAND

1/16 Export Drive, MOLENDINAR
QLD 4214
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

SOUTH AUSTRALIA

30C Richard Street
Hindmarsh, SA, 5007
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses."



@DUROTECHINDUSTRIES.COM.AU