

DUROTECH™ XYLENE

GENERAL PURPOSE THINNER



DESCRIPTION

DUROTECH™ XYLENE is a general purpose thinner. DUROTECH™ XYLENE is used primarily for cleaning of equipment and softening existing membranes to assist in removal.

Under certain circumstances it may be used for thinning down polyurethane membranes.

Can be used to clean the surface of existing polyurethane membranes by applying and wiping off straight away with a clean cloth.

Do not allow to pond.

Allow 20 minutes before applying new membrane.

TECHNICAL INFORMATION

Colour	Clear
Flash Point	21 - 27°C
Packging	4 & 20 Litre
Weather Resistance	2000 hours QUV, no crazing, spalling or softening
Flammability	Highly Flammable
Shelf Life	12 months in unopened containers stored at 20°C

CAUTIONS

Highly Flammable. Keep away from ignition sources (including sparks, flames, pilot lights, gas heaters etc.).

USE ONLY IN WELL VENTILATED AREAS.

Wear protective clothing and do not allow unnecessary contact with skin.

Refer to Durotech MSDS prior to use.

Do not allow to pool or pond on bitumen surfaces, e.g. roofing membranes or bitumen coated damp course.

VICTORIA

34 Indian Drive Keysborough
Victoria 3173
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

NEW SOUTH WALES

14 Essex st, Minto, Sydney
NSW 2566
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

QUEENSLAND

1/16 Export Drive, MOLENDINAR
QLD 4214
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

SOUTH AUSTRALIA

30C Richard Street
Hindmarsh, SA, 5007
Tel: 1300 434 272
sales@durotechindustries.com.au
www.durotechindustries.com.au

