

DUROSIL DS100

NEUTRAL SANITARY SILICONE SEALANT



DESCRIPTION

Durosil DS 100 is a versatile, one component, 100% silicone sealant for sealing building joints and glazing systems and has excellent UV and weather resistance. Ds100 cures with atmospheric moisture to form a durable rubber seal.

FEATURES

- Antifungal and Antibacterial.
- Excellent UV and weather resistance.
- Advanced sanitary features allow usage in high condensation areas.

USES

Durosil DS 100 is suitable for:

- Kitchens, bathrooms, and showers.
- Joint sealing to precast concrete and brickwork.
- Industrial applications where growth of fungi need to be controlled.
- Perimeter and curtain wall sealing, glazing systems and cap beading.

COLOURS

- Translucent
- White
- Off White
- Pebble
- Honey Oak
- Latte
- Sand
- Taupe
- Dark Cocoa
- Black
- Coffee
- Tile Grey
- Grey Mist
- Dune Berry
- Steel Grey
- Slate Grey
- Smoke Grey
- Bluestone
- ONYX Grey

TECHNICAL SPECIFICATION

Physical Properties	Test Method	Typical Value
Cure Mechanism	-	Moisture Cure
Chemistry	-	Neutral Oxime
Specific Gravity,@ 25°C g/ml	ASTM D1475	1.03 ± 0.02
Skin Over Time,@ 25°C, Minutes	-	2 - 5
Rheological Flow @ RT	ASTM C639	Non-sag
Curing rate, at RT mm/day	-	>2
Tensile Strength (N/mm ²)	ASTM D 412	0.7 - 1.0
Elongation at break , %	ASTM D 412	300 - 500
Hardness, Shore A	ASTM D2240	25 - 30
Tear Resistance (N/mm)	ASTM D624	4 - 6
Service Temperature (°C)		-40 to +150
Application Temperature (°C)		+5 to +40

PACKAGING

- 300ml cartridge.



SURFACE PREPARATION

Surface must be clean, dry & free of dirt, dust, grease, oil, mildew, wax, loose paint, frost & old caulking. Clean metal surfaces may be primed for the best results. To achieve the best results, apply only when sealant, air & substrate temperatures are between +5°C to +40°C.

DIRECTIONS

- Clip off tip of nozzle @ 45°angle to desired size
- Use only in well-ventilated areas.
- Masking tape along joint sides will assure straight edge & neat appearance.
- Apply using steady, even pressure to completely bridge joints.
- Smooth sealant using back of spoon dipped in solution of soapy water, for a neat appearance.
- Wipe away excess with a paper towel before surface skins.
- Protect from water until cured (usually 24 hrs.).
Note: SEALANT NOT PAINTABLE. Complete painting prior to application of sealant.

CLEAN UP

Use dry Paper Towel/Rag or Mineral Spirits for cleaning before the sealant cures.

LIMITATIONS

- Sealant not paintable.
- Requires Solvent Clean-up.

FOR BEST RESULTS

- Complete all painting prior to sealant application.
- Apply only to properly prepared surfaces; siliconewill not adhere to itself or to other sealants; surface air & substrate temperature between +5°C and +40°C.
- Tool the applied bead with back of spoon, dipped in soapy water.
- Clean up solvent before cure with mineral spirits; after cure remove excess with razor blade; avoid undercutting seal.

STORAGE AND SHELF LIFE

Durosil DS 100 has a shelf life of 12 months from the date of production when stored in the original unopened containers at or below 25°C. In countries where high heat and humidity are a factor, special precautions must be taken to store the product in a covered, well-ventilated warehouse and avoid excessive heat conditions.

SAFETY

Safety data sheet available upon request.

Durotech Industries Pty Ltd

Address	14 Essex Street, P.O Box 5092, Minto, NSW 2566
Phone	+61 2 9603 1177
Fax	+61 2 9475 5059
Email	sales@durotechindustries.com.au
Web	www.durotechindustries.com.au

DUROTECH INDUSTRIES



"This document, including any attached files, is strictly confidential and intended solely for the use of the individual or entity to which it is addressed. Durotech Industries prohibits the right to publish, copy, distribute or disclose any information contained in this document, or its attachments, by any party other than the intended recipient. If you have received this document in error please notify the sender and delete it from your system immediately. no employee or agent is authorised to conclude any binding agreement or make any representation on behalf of Durotech Industries. The views or opinions presented in this document are solely those of the author and do not necessarily represent those of Durotech Industries, except where the sender expressly, and with clear authority, states them to be the views of Durotech Industries. Durotech Industries accepts no liability for any loss or damage (direct or indirect or consequential) arising from the use of or in connection with this document and any attachments and suggests that the recipient check this document and any attached files for the presence of viruses."

